

Surface Mount Type

Series : **FT** Type : **V**

High temperature Lead-Free reflow



Features

- Endurance : 105 °C 2000 h to 5000 h
- Miniaturized, Low ESR (1 size smaller than series FK)
- Vibration-proof product is available upon request. (φ8 mm and larger)
- RoHS compliant

Specifications


Category temperature range	-55 °C to +105 °C	
Rated voltage range	6.3 V.DC to 50 V.DC	
Rated capacitance range	10 μF to 2200 μF	
Capacitance tolerance	±20 % (120 Hz/+20 °C)	
Leakage current	$I \leq 0.01 CV$ After 2 minutes	
Dissipation factor (tan δ)	Please see the attached characteristics list	
Endurance	After applying rated working voltage for 2000 hours at +105 °C±2 °C and then being stabilized at +20 °C, Capacitors shall meet the following limits. (Suffix "G" in 6.3 V.DC : 3000 hours, 10 V.DC to 50 V.DC : 5000 hours)	
	Capacitance change	Within ±30 % of the initial value (Suffix "G" is ±35 %)
	tan δ	≤200 % of the initial limit (Suffix "G" is ≤300 %)
Shelf life	DC leakage current	Within the initial limit
	After storage for 1000 hours at +105 °C±2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance. (With voltage treatment)	
Resistance to soldering heat	After reflow soldering and then being stabilized at +20 °C, capacitor shall meet the following limits.	
	Capacitance change	Within ±10 % of the initial value
	tan δ	Within the initial limit
AEC-Q200	DC leakage current	Within the initial limit
	AEC-Q200 compliant	

Frequency correction factor for ripple current

Frequency (Hz)	120	1 k	10 k	100 k to
Capacitance (μF)				
10 to 470	0.65	0.85	0.95	1.00
560 to 2200	0.70	0.90	0.95	1.00


Marking

Example : 25 V.DC 22 μF
Marking color : BLACK



R. Voltage (V.DC)	6.3	10	16	25	35	50
Code	j	A	C	E	V	H

Dimensions



() Reference size
(Unit : mm)

Size code	φD	L	A, B	H	I	W	P	K
B	4.0	5.8±0.3	4.3	5.5 max.	1.8	0.65±0.1	1.0	0.35 ^{+0.15} _{-0.20}
C	5.0	5.8±0.3	5.3	6.5 max.	2.2	0.65±0.1	1.5	0.35 ^{+0.15} _{-0.20}
D	6.3	5.8±0.3	6.6	7.8 max.	2.6	0.65±0.1	1.8	0.35 ^{+0.15} _{-0.20}
D8	6.3	7.7±0.3	6.6	7.8 max.	2.6	0.65±0.1	1.8	0.35 ^{+0.15} _{-0.20}
F	8.0	10.2±0.3	8.3	10.0 max.	3.4	0.90±0.2	3.1	0.70±0.20
G	10.0	10.2±0.3	10.3	12.0 max.	3.5	0.90±0.2	4.6	0.70±0.20

Characteristics list

Endurance : 105 °C 2000 h

Rated voltage (V.DC)	Cap. (±20 %) (μF)	Case size (mm)		Size* code	Specification			Part No.	Reflow	Min. Packaging Q'ty
		φD	L		Ripple current (100 kHz) (+105 °C) (mA r.m.s.)	ESR (100 kHz) (+20 °C) (Ω)	tan δ (120 Hz) (+20 °C)			Taping (pcs)
6.3	100	4	5.8	B	160	0.85	0.26	EEEF0J101AR	(5)	2000
	220	5	5.8	C	240	0.36	0.26	EEEF0J221AR	(5)	1000
	330	6.3	5.8	D	300	0.26	0.26	EEEF0J331AP	(5)	1000
	470	6.3	7.7	D8	600	0.16	0.26	EEEF0J471XAP	(5)	900
	680	6.3	7.7	D8	600	0.16	0.26	EEEF0J681XAP	(5)	900
	1500	8	10.2	F	850	0.08	0.26	EEEF0J152AP	(6)	500
	2200	10	10.2	G	1190	0.06	0.28	EEEF0J222AP	(6)	500
10	68	4	5.8	B	160	0.85	0.19	EEEF1A680AR	(5)	2000
	150	5	5.8	C	240	0.36	0.19	EEEF1A151AR	(5)	1000
	220	6.3	5.8	D	300	0.26	0.19	EEEF1A221AP	(5)	1000
	330	6.3	7.7	D8	600	0.16	0.19	EEEF1A331XAP	(5)	900
	470	6.3	7.7	D8	600	0.16	0.19	EEEF1A471XAP	(5)	900
	1000	8	10.2	F	850	0.08	0.19	EEEF1A102AP	(6)	500
	1500	10	10.2	G	1190	0.06	0.19	EEEF1A152AP	(6)	500
16	47	4	5.8	B	160	0.85	0.16	EEEF1C470AR	(5)	2000
	68	5	5.8	C	240	0.36	0.16	EEEF1C680AR	(5)	1000
	100	5	5.8	C	240	0.36	0.16	EEEF1C101AR	(5)	1000
	150	6.3	5.8	D	300	0.26	0.16	EEEF1C151AP	(5)	1000
	220	6.3	5.8	D	300	0.26	0.16	EEEF1C221AP	(5)	1000
	330	6.3	7.7	D8	600	0.16	0.16	EEEF1C331XAP	(5)	900
	680	8	10.2	F	850	0.08	0.16	EEEF1C681AP	(6)	500
	1000	10	10.2	G	1190	0.06	0.16	EEEF1C102AP	(6)	500
25	22	4	5.8	B	160	0.85	0.14	EEEF1E220AR	(5)	2000
	33	4	5.8	B	160	0.85	0.14	EEEF1E330AR	(5)	2000
	47	5	5.8	C	240	0.36	0.14	EEEF1E470AR	(5)	1000
	68	5	5.8	C	240	0.36	0.14	EEEF1E680AR	(5)	1000
	100	6.3	5.8	D	300	0.26	0.14	EEEF1E101AP	(5)	1000
	150	6.3	7.7	D8	600	0.16	0.14	EEEF1E151XAP	(5)	900
	220	6.3	7.7	D8	600	0.16	0.14	EEEF1E221XAP	(5)	900
	470	8	10.2	F	850	0.08	0.14	EEEF1E471AP	(6)	500
	820	10	10.2	G	1190	0.06	0.14	EEEF1E821AP	(6)	500
35	22	4	5.8	B	160	0.85	0.12	EEEF1V220AR	(5)	2000
	33	5	5.8	C	240	0.36	0.12	EEEF1V330AR	(5)	1000
	47	5	5.8	C	240	0.36	0.12	EEEF1V470AR	(5)	1000
	68	6.3	5.8	D	300	0.26	0.12	EEEF1V680AP	(5)	1000
	100	6.3	5.8	D	300	0.26	0.12	EEEF1V101AP	(5)	1000
	150	6.3	7.7	D8	600	0.16	0.12	EEEF1V151XAP	(5)	900
	330	8	10.2	F	850	0.08	0.12	EEEF1V331AP	(6)	500
	560	10	10.2	G	1190	0.06	0.12	EEEF1V561AP	(6)	500
50	10	4	5.8	(B)	85	2.30	0.10	EEEF1H100UAR	(5)	2000
		5	5.8	C	165	0.88	0.10	EEEF1H100AR	(5)	1000
	22	5	5.8	C	165	0.88	0.10	EEEF1H220AR	(5)	1000
	47	6.3	5.8	D	195	0.68	0.10	EEEF1H470AP	(5)	1000
	100	6.3	7.7	D8	350	0.34	0.10	EEEF1H101XAP	(5)	900
	220	8	10.2	F	670	0.18	0.10	EEEF1H221AP	(6)	500
	330	10	10.2	G	900	0.12	0.10	EEEF1H331AP	(6)	500

* Size code() : Miniaturization product

If Part number exceeds 12 digits, voltage code is abbreviated as follows; 0J → J, 1A → A, 1C → C, 1E → E, 1V → V, 1H → H

· Please refer to the page of "Reflow Profile" and "The Taping Dimensions".

· When requesting vibration-proof product, please put the last "V" instead to "P"

Characteristics list (Endurance 5000 h)

Endurance : 105 °C 5000 h (6.3 V.DC : 105 °C 3000 h)

Rated voltage (V.DC)	Cap. (±20 %) (μF)	Case size (mm)		Size code	Specification			Part No.	Reflow	Min. Packaging Q'ty
		φD	L		Ripple current (100 kHz) (+105 °C) (mA r.m.s.)	ESR (100 kHz) (+20 °C) (Ω)	tan δ (120 Hz) (+20 °C)			Taping (pcs)
6.3	NEW 1500	8	10.2	F	850	0.08	0.26	EEEFT0J152GP	(6)	500
	NEW 2200	10	10.2	G	1190	0.06	0.28	EEEFT0J222GP	(6)	500
10	NEW 1000	8	10.2	F	850	0.08	0.19	EEEFT1A102GP	(6)	500
	NEW 1500	10	10.2	G	1190	0.06	0.19	EEEFT1A152GP	(6)	500
16	NEW 680	8	10.2	F	850	0.08	0.16	EEEFT1C681GP	(6)	500
	NEW 1000	10	10.2	G	1190	0.06	0.16	EEEFT1C102GP	(6)	500
25	NEW 470	8	10.2	F	850	0.08	0.14	EEEFT1E471GP	(6)	500
	NEW 820	10	10.2	G	1190	0.06	0.14	EEEFT1E821GP	(6)	500
35	NEW 330	8	10.2	F	850	0.08	0.12	EEEFT1V331GP	(6)	500
	NEW 560	10	10.2	G	1190	0.06	0.12	EEEFT1V561GP	(6)	500
50	NEW 220	8	10.2	F	670	0.18	0.10	EEEFT1H221GP	(6)	500
	NEW 330	10	10.2	G	900	0.12	0.10	EEEFT1H331GP	(6)	500

- Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
- When requesting vibration-proof product, please put the last "V" instead to "P"

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[EEE-FT0J331AP](#) [EEE-FT0J222AP](#) [EEE-FT1C101AR](#) [EEE-FT1A680AR](#) [EEE-FT1A221AP](#) [EEE-FT1A152AP](#) [EEE-FT1A151AR](#) [EEE-FT0J221AR](#) [EEE-FT0J152AP](#) [EEE-FT0J101AR](#) [EEE-FT1A102AP](#)