


SP3008UB

[Home](#) > [Broadband • ADSL & VDSL](#) > [ADSL and Broadband](#) > [ADSL and Broadband](#)



## 56K Data/Fax USB Modem



Model No. SP3008UB

- Interface: USB 1.1 interface for PC connection and RJ-11 jack for telephone line
- Data speed: 56000(downstream), 33600, 31200, 28800, 26400, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, 2400, 1200 and 300bps

Micronet 56K USB modem SP3008UB provides you the convenient way to access Internet, and fax electric file without having fax machine actually. It adapts the newest chipset technology to enhance the connection stability and full modem functions. It's really the ultimate petite box of 56K modem.



### Overview

- Interface: USB 1.1 interface for PC connection and RJ-11 jack for telephone line
- Data compatibility: ITU-T V.92, V.90, V.34, V.32, V.32bis, V.22bis and V.21, Bell 212A and 103
- Data speed: 56000(downstream), 33600, 31200, 28800, 26400, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, 2400, 1200 and 300bps
- Receiving rate: up to 56Kbps and transmit rate up to 33.6Kbps
- Fax compatibility: ITU-T V.29, V.27ter, V.17 and V.21 ch2; Class 1 Group 3
- Fax speed: 14400, 12000, 9600, 7200, 4800, 2400bps; sending and receiving rate up to 14.4Kbps
- Error correction: MNP 2-4, ITU-T V.42
- Data compression: MNP 5, ITU-T V.44, V.42bis
- DTE speed: 115,200bps
- Supports Telephone Answering Machine(TAM) with concurrent DTMF detect, Ring Detect and Caller ID
- Caller ID: Caller ID detect; On-Hook Caller ID detection
- Dial type: Tone and Pulse
- AT command set
- Operating system: Windows 98SE/Me/2000/XP/Vista ; Linux
- 
- 

### • Specification

Model	SP3008UB
Data Transfer Rate	Up to 56 Kbps download and 48 Kbps upload
Data Transmission	ITU-T V.92,

	V.90, V.34, V.32, V.32bis, V.22bis and V.21, Bell 212A and 103
Data Compression	MNP 5, ITU-T V.44, V.42bis
Error Correction	MNP 2-4, ITU-T V.42 V.17, V.29, V.27ter, and
Fax Transmission	V.21 channel 2 EIA/TIA 578 Class 1 and T.31 Class 1.0 commands
Fax Transfer Rate	Up to 14.4 Kbps send and receive
Voice	Telephone Answering Machine (TAM)
Interface	RJ-11 Line
Command Set	AT Command Set Pentium MMX 450MHz
System Requirement	64M RAM or above 1 spare USB port
Driver Support	Windows 98SE/Me/2000/XP/Vista, Linux
Dimension (mm)	75 x 25 x 17
Weight (g)	32
Emission	FCC,CE

- Ordering Information
- SP3008UB: 56K Data/Fax USB Modem, V.92
-