



N-Channel 60-V (D-S) MOSFETs with Zener Gate

PRODUCT SUMMARY				
Part Number	$V_{(BR)DSS}$ Min (V)	$r_{DS(on)}$ Max (Ω)	$V_{GS(th)}$ (V)	I_D (A)
VN0610L	60	5 @ $V_{GS} = 10$ V	0.8 to 2.5	0.27
VN10KLS		5 @ $V_{GS} = 10$ V	0.8 to 2.5	0.31
VN2222L		7.5 @ $V_{GS} = 10$ V	0.6 to 2.5	0.23

FEATURES



- Zener Diode Input Protected
- Low On-Resistance: 3 Ω
- Ultralow Threshold: 1.2 V
- Low Input Capacitance: 38 pF
- Low Input and Output Leakage

BENEFITS



- Extra ESD Protection
- Low Offset Voltage
- Low-Voltage Operation
- High-Speed, Easily Driven
- Low Error Voltage

APPLICATIONS

- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays
- Inductive Load Drivers

Device Marking
Front View

"S" = Siliconix Logo
xxyy = Date Code

Device Marking
Front View

"S" = Siliconix Logo
xxyy = Date Code

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter	Symbol	VN2222L VN0610L	VN10KLS	Unit
Drain-Source Voltage	V_{DS}	60	60	V
Gate-Source Voltage	V_{GS}	15/-0.3	15/-0.3	
Continuous Drain Current ($T_J = 150^\circ\text{C}$)	I_D	0.27	0.31	A
		0.17	0.20	
Pulsed Drain Current ^a	I_{DM}	1	1.0	
Power Dissipation	P_D	0.8	0.9	W
		0.32	0.4	
Thermal Resistance, Junction-to-Ambient	R_{thJA}	156	139	$^\circ\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150		$^\circ\text{C}$

Notes

a. Pulse width limited by maximum junction temperature.







SPECIFICATIONS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)






Parameter	Symbol	Test Conditions	Typ ^a	Limits				Unit
				VN0610L VN10KLS		VN2222L		
				Min	Max	Min	Max	
Static								
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 100 μA	120	60		60		V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 1 mA	1.2	0.8	2.5	0.6	2.5	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = 15 V	1		100		100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 48 V, V _{GS} = 0 V			10		10	μA
		T _J = 125°C			500		500	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 10 V, V _{GS} = 10 V	1	0.75		0.75		A
Drain-Source On-Resistance ^b	r _{DS(on)}	V _{GS} = 5 V, I _D = 0.2 A	4		7.5		7.5	Ω
		V _{GS} = 10 V, I _D = 0.5 A	3		5		7.5	
		T _J = 125°C	5.6		9		13.5	
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 0.5 A	300	100		100		mS
Common Source Output Conductance ^b	g _{os}	V _{DS} = 7.5 V, I _D = 0.05 A	0.2					
Dynamic								
Input Capacitance	C _{iss}	V _{DS} = 25 V, V _{GS} = 0 V, f = 1 MHz	38		60		60	pF
Output Capacitance	C _{oss}		16		25		25	
Reverse Transfer Capacitance	C _{rss}		2		5		5	
Switching ^c								
Turn-On Time	t _{ON}	V _{DD} = 15 V, R _L = 23 Ω I _D ≅ 0.6 A, V _{GEN} = 10 V R _G = 25 Ω	7		10		10	ns
Turn-Off Time	t _{OFF}		9		10		10	

Notes

- a. For DESIGN AID ONLY, not subject to production testing.
b. Pulse test: $PW \leq 300\text{ }\mu\text{s}$ duty cycle $\leq 2\%$.
c. Switching time is essentially independent of operating temperature.

VNDP06

**TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)****Ohmic Region Characteristics****Output Characteristics for Low Gate Drive****Transfer Characteristics****On-Resistance vs. Gate-to-Source Voltage****On-Resistance vs. Drain Current****Normalized On-Resistance vs. Junction Temperature**

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)




Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)
[VN10KLS](#)