

ATC 600F Series

Ultra-Low ESR, High Q, NPO RF & Microwave Capacitors

Features:

- **Lowest ESR in Class**
- Highest Working Voltage in class – 250V
- Standard EIA Size: 0805
- Laser Marking (Optional)
- High Self Resonance Frequencies

Applications:

- Cellular Base Stations
- Wireless Communications
- Broadband Wireless Services
- Satellite Communications
- WiMAX (802.16)

Circuit Applications:

- Filter Networks
- High Q Frequency Sources
- Matching Networks
- Tuning, Coupling, Bypass and DC Blocking



ATC 600 SERIES OVERVIEW

ATC Series	ATC Case Size	EIA Case Size
600	L	0402
600	S	0603
600	F	0805

Electrical Specifications

Capacitance:	0.1 to 240 pF
Tolerances:	See Cap Value Chart
Working Voltage (WVDC):	250 V
Quality Factor (Q):	> 2000 @ 1 MHz
Operating Temperature Range:	-55°C to +125°C (no derating of working voltage)
Temperature coefficient of Capacitance (TCC):	0 ± 30 ppm/°C, -55°C to +125°C
Insulation Resistance:	10 ⁵ MΩ min. at +25°C at rated WVDC 10 ⁴ MΩ min. at +125°C at rated WVDC
Dielectric Withstanding Voltage (DWV):	2.5 x WVDC for 5 seconds
Aging:	None
Piezo Effects:	None

Mechanical Specifications

Terminations:	T = Tin Plated over Nickel Barrier* (Standard) TN = Tin Plated over Non-Magnetic Barrier* W = Tin/Lead Solder Plated over Nickel Barrier
Solderability:	Solder coverage > 90% of end termination
Terminal Strength:	4 lbs. Typ., 2 lbs. min.

Environmental Specifications

Life Test:	2000 hours, +125°C at 2X WVDC
Thermal Shock:	5 cycles, -55°C to +125°C
Moisture Resistance:	240 hours, 85% Relative Humidity at +85°C

Military Approval

DSCC Drawing Number 05001



ATC 600 Series Capacitors are designed and manufactured to meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123.



A M E R I C A N

ATC North America

sales@atceramics.com

T E C H N I C A L

ATC Europe

saleseur@atceramics.com

C E R A M I C S

ATC Asia

sales@atceramics-asia.com



ISO 9001
REGISTERED
COMPANY

www.atceramics.com

ATC # 001-956
Rev. M; 12/09

ATC 600F Series Ultra-Low ESR, High Q NPO RF & Microwave Capacitors

Capacitance Values*

Value (pF)	Cap Code	Marking	Tolerances	Value (pF)	Cap Code	Marking	Tolerances	Value (pF)	Cap Code	Marking	Tolerances
0.1	0R1	A9	A, B	3.3	3R3	N0	A, B, C, D	30	300	M1	F, G, J, K, M
0.2	0R2	H9	A, B	3.6	3R6	P0	A, B, C, D	33	330	N1	F, G, J, K, M
0.3	0R3	M9	A, B, C	3.9	3R9	Q0	A, B, C, D	36	360	P1	F, G, J, K, M
0.4	0R4	d9	A, B, C	4.3	4R3	R0	A, B, C, D	39	390	Q1	F, G, J, K, M
0.5	0R5	f9	A, B, C	4.7	4R7	S0	A, B, C, D	43	430	R1	F, G, J, K, M
0.6	0R6	m9	A, B, C	5.1	5R1	T0	A, B, C, D	47	470	S1	F, G, J, K, M
0.7	0R7	n9	A, B, C	5.6	5R6	U0	A, B, C, D	51	510	T1	F, G, J, K, M
0.8	0R8	t9	A, B, C	6.2	6R2	V0	A, B, C, D	56	560	U1	F, G, J, K, M
0.9	0R9	y9	A, B, C	6.8	6R8	W0	B, C, J, K	62	620	V1	F, G, J, K, M
1.0	1R0	A0	A, B, C, D	7.5	7R5	X0	B, C, J, K	68	680	W1	F, G, J, K, M
1.1	1R1	B0	A, B, C, D	8.2	8R2	Y0	B, C, J, K	75	750	X1	F, G, J, K, M
1.2	1R2	C0	A, B, C, D	9.1	9R1	Z0	B, C, J, K	82	820	Y1	F, G, J, K, M
1.3	1R3	D0	A, B, C, D	10	100	A1	F, G, J, K, M	91	910	Z1	F, G, J, K, M
1.5	1R5	E0	A, B, C, D	11	110	B1	F, G, J, K, M	100	101	A2	F, G, J, K, M
1.6	1R6	F0	A, B, C, D	12	120	C1	F, G, J, K, M	110	111	B2	F, G, J, K, M
1.8	1R8	G0	A, B, C, D	15	150	E1	F, G, J, K, M	120	121	C2	F, G, J, K, M
2.0	2R0	H0	A, B, C, D	18	180	G1	F, G, J, K, M	150	151	E2	F, G, J, K, M
2.2	2R2	J0	A, B, C, D	20	200	H1	F, G, J, K, M	180	181	G2	F, G, J, K, M
2.4	2R4	K0	A, B, C, D	22	220	J1	F, G, J, K, M	200	201	H2	F, G, J, K, M
2.7	2R7	L0	A, B, C, D	24	240	K1	F, G, J, K, M	220	221	J2	F, G, J, K, M
3.0	3R0	M0	A, B, C, D	27	270	L1	F, G, J, K, M	240	241	K2	F, G, J, K, M

*Non-standard values and custom tolerances are available upon request.

ATC Part Number Code

ATC Series 600 Case Size (0805) F Capacitance Code: 10 0 Indicates number of zeros following digits of capacitance in picofarads except for decimal values. Capacitance Tolerance J T 250 X T

First 2 significant digits for capacitance. R=Decimal Point

Indicates number of zeros following digits of capacitance in picofarads except for decimal values.

Capacitance Tolerance

Termination Code

WVDC

Lasers Marked**

Packaging

T - Tape and Reel (Standard)*

TV - Vertical Tape and Reel (Optional)

T = Tin Plated over Nickel Barrier (Standard) RoHS Compliant

TN = Tin Plated over Non-Magnetic Barrier

W = Tin/Lead Solder Plated over Nickel Barrier

Code	A	B	C	D	F	G	J	K	M
Tol.	±0.05 pF	±0.1 pF	±0.25 pF	±0.5 pF	±1%	±2%	±5%	±10%	±20%

*4,000 pieces on 7" reel and 500 pieces on prototype reel. Consult ATC for other options.

The above part number refers to a 600F Series (case size F) 10 pF capacitor, J tolerance (±5%), 250 WVDC, with T termination (Tin Plated over Nickel Barrier, RoHS Compliant), Laser Marking and Tape and Reel packaging.

** Marking is optional.

ATC accepts orders for our parts using designations **with** or **without** the "ATC" prefix. Both methods of defining the part number are equivalent, i.e., part numbers referenced with the "ATC" prefix are interchangeable to parts referenced without the "ATC" prefix. Customers are free to use either in specifying or procuring parts from American Technical Ceramics.

For additional information and catalogs contact your ATC representative or call direct at (+1-631) 622-4700.

Consult factory for 500 piece reels for prototyping.

Consult factory for additional performance data.



A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America
sales@atceramics.com

ATC Europe
sales@atceramics.com

ATC Asia
sales@atceramics-asia.com

ATC 600F Series Ultra-Low ESR, High Q NPO RF & Microwave Capacitors



ATC 600F Series Data Sheet Test Condition Description

Capacitors horizontally mounted on 23.3-mil thick Rogers RO4350® softboard, 52-mil wide, 1/2 oz. Cu traces.

FSR = lowest frequency at which S11 response, referenced at capacitor edge, crosses real axis on Smith Chart.

FPR = lowest frequency at which there is a notch in S21 magnitude response.

A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America
sales@atceramics.com

ATC Europe
saleseur@atceramics.com

ATC Asia
sales@atceramics-asia.com

www.atceramics.com

ATC 600F Series Ultra-Low ESR, High Q NPO RF & Microwave Capacitors

Outline Dimensions

	F (0805) L: .079 ± .008 (2.01 ± 0.20) W: .049 ± .008 (1.24 ± 0.20)	T: .051 max. (1.30 max.) Y: .020 ± 0.01 (0.51 ± 0.25)
Inches (mm)		

Suggested Mounting Pad Dimensions

<p>Horizontal Electrode Orientation</p> <p>Vertical Electrode Orientation</p>		Case Sizes L, S and F				
Case Size		A Min.	B Min.	C Min.	D Min.	
0402 (1005)		.0275 (0.70)	.0354 (0.90)	.0157 (0.40)	.0866 (2.20)	
0603 (1608)		.0393 (1.00)	.0433 (1.10)	.0236 (0.60)	.110 (2.80)	
0805 (2012)		.0590 (1.50)	.0512 (1.30)	.0236 (0.60)	.1259 (3.20)	
						Inches (mm)

Design Kits Each Kit contains a selection of standard capacitor values for circuit prototyping.

Kit #	Item #	Description	Cap. Value Range (pF)	Cap. Values (pF)	Tol. (pF)	Price
Kit 32T	DK0032T 	600F Series Ultra-low ESR, High Q Microwave Capacitors 16 different values, 15 pcs. min. per value	0.1 to 2.0	0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.1, 1.2, 1.5	±0.1	\$90.00
				1.6, 1.8, 2.0	±0.25	
Kit 33T	DK0033T 	600F Series Ultra-low ESR, High Q Microwave Capacitors 16 different values, 15 pcs. min. per value	1.0 to 10	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3	±0.1	\$90.00
				3.9, 4.7, 5.6, 6.8, 8.2	±0.25	
				10	±5%	
Kit 34T	DK0034T 	600F Series Ultra-low ESR, High Q Microwave Capacitors 16 different values, 15 pcs. min. per value	10 to 100	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100	±5%	\$90.00
Kit 35T	DK0035T 	600F Series Ultra-low ESR, High Q Microwave Capacitors 7 different values, 15 pcs. min. per value	100 to 240	100, 120, 150, 180, 200, 220, 240	±5%	\$50.00

For Online Kit Orders, Catalog & Application Notes, Visit: www.atceramics.com

Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale(ATC document #001-992 Rev. B 12/05). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at www.atceramics.com/productfinder/default.asp. Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 2002 American Technical Ceramics Corp. All Rights Reserved.

ATC 001-956 Rev. M; 12/09

A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America
sales@atceramics.com

ATC Europe
sales@atceramics.com

ATC Asia
sales@atceramics-asia.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

American Technical Ceramics (ATC):

[600F120FT250XT](#) [600F241JT250XT](#) [600F180FT250XT](#) [600F0R2AT250XT](#) [600F3R9CT250XT](#) [600F1R5BT250XT](#)
[600F510JT250XT](#) [600F680JT250XT](#) [600F0R7AT250XT](#) [600F2R2AW250XT](#) [600F390JT250XT](#) [600F101JT250XT](#)
[600F8R2BT250XT](#) [600F2R4BT250XT](#) [600F0R8BT250XT](#) [600F1R0AT250XT](#) [600F100GT250XT](#) [600F6R8CT250XT](#)
[600F0R3BT250XT](#) [600F150FT250XT](#) [600F1R2AT250XT](#) [600F2R0AT250XT](#) [600F0R5AT250XT](#) [600F9R1JT250XT](#)
[600F1R8AT250XT](#) [600F3R0CT250XT](#) [600F120JT250XT](#) [600F7R5BT250XT](#) [600F910JT250XT](#) [600F201JT250XT](#)
[600F0R4AT250XT](#) [600F121FT250XT](#) [600F470FT250XT](#) [600F470JT250XT](#) [600F430FT250XT](#) [600F9R1BT250XT](#)
[600F1R8BT250XT](#) [600F1R2BT250XT](#) [600F2R7AT250XT](#) [600F6R8JT250XT](#) [600F0R9BT250XT](#) [600F560FT250XT](#)
[600F5R1CT250XT](#) [600F7R5JT250XT](#) [600F3R0AT250XT](#) [600F150GT250XT](#) [600F0R6AT250XT](#) [600F0R5BT250XT](#)
[600F2R0BT250XT](#) [600F5R6AT250XT](#) [600F5R6CT250XT](#) [600F3R3BT250XT](#) [600F100JT250XT](#) [600F4R7AT250XT](#)
[600F200JT250XT](#) [600F220JT250XT](#) [600F330FT250XT](#) [600F9R1CT250XT](#) [600F100FT250XT](#) [600F4R3BT250XT](#)
[600F8R2CT250XT](#) [600F0R7BT250XT](#) [600F270JT250XT](#) [600F0R1AT250XT](#) [600F2R0CT250XT](#) [600F1R5CT250XT](#)
[600F390FT250XT](#) [600F680FT250XT](#) [600F3R9AT250XT](#) [600F2R2BT250XT](#) [600F150JT250XT](#) [600F3R3CT250XT](#)
[600F4R7BT250XT](#) [600F240FT250XT](#) [600F221JT250XT](#) [600F330JT250XT](#) [600F2R7CT250XT](#) [600F101GT250XT](#)
[600F151JT250XT](#) [600F1R5AT250XT](#) [600F680GT250XT](#) [600F0R1BT250XT](#) [600F390GT250XT](#) [600F4R3CT250XT](#)
[600F0R8AT250XT](#) [600F1R0BT250XT](#) [600F1R6BT250XT](#) [600F430JT250XT](#) [600F0R3AT250XT](#) [600F181FT250XT](#)
[600F220FT250XT](#) [600F3R9BT250XT](#) [600F6R8BT250XT](#) [600F101FT250XT](#) [600F241FT250XT](#) [600F750JT250XT](#)
[600F0R4BT250XT](#) [600F2R7BT250XT](#) [600F820FT250XT](#) [600F180JT250XT](#)