


# Fast Recovery Epitaxial Diode (FRED)


**DSEI 30**

**$I_{FAVM} = 30\text{ A}$**   
 **$V_{RRM} = 1000\text{ V}$**   
 **$t_{rr} = 35\text{ ns}$**


$V_{RSM}$ V	$V_{RRM}$ V	Type
1000	1000	DSEI 30-10A
1000	1000	DSEI 30-10AR



**TO-247 AD**  
Version A



**ISOPLUS 247™**  
Version AR



A = Anode, C = Cathode

\* Patent pending

Symbol	Test Conditions	Maximum Ratings	
$I_{FRMS}$ $I_{FAVM}$ ① $I_{FRM}$	$T_{VJ} = T_{VJM}$ $T_C = 85^\circ\text{C}$ ; rectangular, $d = 0.5$ $t_p < 10\text{ }\mu\text{s}$ ; rep. rating, pulse width limited by $T_{VJM}$	70 30 375	A A A
$I_{FSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	200	A
	$t = 8.3\text{ ms}$ (60 Hz), sine	210	A
	$T_{VJ} = 150^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	185	A
	$t = 8.3\text{ ms}$ (60 Hz), sine	195	A
$I^2t$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	200	A <sup>2</sup> s
	$t = 8.3\text{ ms}$ (60 Hz), sine	180	A <sup>2</sup> s
	$T_{VJ} = 150^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	170	A <sup>2</sup> s
	$t = 8.3\text{ ms}$ (60 Hz), sine	160	A <sup>2</sup> s
$T_{VJ}$		-40...+150	°C
$T_{VJM}$		150	°C
$T_{stg}$		-40...+150	°C
$P_{tot}$	$T_C = 25^\circ\text{C}$	138	W
$M_d^*$ $F_C$	Mounting torque mounting force with clip	0.8...1.2 20...120	Nm N
$V_{ISOL}^{**}$	50/60 Hz, RMS, $t = 1\text{ minute}$ , leads-to-tab	2500	V~
<b>Weight</b>		6	g

\* Version A only; \*\* Version AR only

Symbol	Test Conditions	Characteristic Values	
		typ.	max.
$I_R$	$T_{VJ} = 25^\circ\text{C}$		750 $\mu\text{A}$
	$T_{VJ} = 25^\circ\text{C}$		250 $\mu\text{A}$
	$T_{VJ} = 125^\circ\text{C}$		7 mA
$V_F$	$I_F = 36\text{ A}$ ; $T_{VJ} = 150^\circ\text{C}$		2 V
	$T_{VJ} = 25^\circ\text{C}$		2.4 V
$V_{T0}$	For power-loss calculations only		1.5 V
$r_T$	$T_{VJ} = T_{VJM}$		12.5 mΩ
$R_{thJC}$ $R_{thCK}$ $R_{thJA}$	0.25		0.9 K/W K/W K/W
$t_{rr}$	$I_F = 1\text{ A}$ ; $-di/dt = 100\text{ A}/\mu\text{s}$ ; $V_R = 30\text{ V}$ ; $T_{VJ} = 25^\circ\text{C}$	35	50 ns
$I_{RM}$	$V_R = 540\text{ V}$ ; $I_F = 30\text{ A}$ ; $-di_F/dt = 240\text{ A}/\mu\text{s}$ $L \leq 0.05\text{ }\mu\text{H}$ ; $T_{VJ} = 100^\circ\text{C}$	16	18 A

①  $I_{FAVM}$  rating includes reverse blocking losses at  $T_{VJM}$ ,  $V_R = 0.8 V_{RRM}$ , duty cycle  $d = 0.5$   
 Data according to IEC 60747

IXYS reserves the right to change limits, test conditions and dimensions

## Features

- International standard package JEDEC TO-247 AD
- Planar passivated chips
- Very short recovery time
- Extremely low switching losses
- Low  $I_{RM}$ -values
- Soft recovery behavior
- Epoxy meets UL 94V-0
- Version AR isolated and UL registered E153432

## Applications

- Antiparallel diode for high frequency switching devices
- Anti saturation diode
- Snubber diode
- Free wheeling diode in converters and motor control circuits
- Rectifiers in switch mode power supplies (SMPS)
- Inductive heating and melting
- Uninterruptible power supplies (UPS)
- Ultrasonic cleaners and welders

## Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses
- Operating at lower temperature or space saving by reduced cooling




Fig. 1 Forward current versus voltage drop.




Fig. 2 Recovery charge versus  $-di_F/dt$ .




Fig. 3 Peak reverse current versus  $-di_F/dt$ .




Fig. 4 Dynamic parameters versus junction temperature.




Fig. 5 Recovery time versus  $-di_F/dt$ .




Fig. 6 Peak forward voltage versus  $di_F/dt$ .





Fig. 7 Transient thermal impedance junction to case.

### Dimensions



Dim.	Millimeter Min. Max.	Inches Min. Max.
A	19.81 20.32	0.780 0.800
B	20.80 21.46	0.819 0.845
C	15.75 16.26	0.610 0.640
D	3.55 3.65	0.140 0.144
E	4.32 5.49	0.170 0.216
F	5.4 6.2	0.212 0.244
G	1.65 2.13	0.065 0.084
H	- 4.5	- 0.177
J	1.0 1.4	0.040 0.055
K	10.8 11.0	0.426 0.433
L	4.7 5.3	0.185 0.209
M	0.4 0.8	0.016 0.031
N	2.2 2.54	0.087 0.102

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[DSEI30-10A](#) [DSEI30-10AR](#)