


## SCHOTTKY BARRIER DIODE

### ■ Outline drawings, mm




### ■ Features

- Low  $V_F$
- Super high speed switching
- High reliability by planer design

### ■ Applications

- High speed power switching

### ■ Marking



### ■ Maximum ratings and characteristics

- Absolute maximum ratings

| Item                            | Symbol      | Conditions  | Rating      | Unit               |
|---------------------------------|-------------|---|-------------|--------------------|
| Repetitive peak reverse voltage | $V_{RRM}$   |   | 90          | V                  |
| Average forward current         | $I_{F(AV)}$ | Square wave, duty=1/2<br>$T_I=85^{\circ}\text{C}^*$ | 3.0         | A                  |
| Surge current                   | $I_{FSM}$   | Sine wave<br>10ms                                   | 120         | A                  |
| Operating junction temperature  | $T_j$       |   | -40 to +150 | $^{\circ}\text{C}$ |
| Storage temperature             | $T_{stg}$   |   | -40 to +150 | $^{\circ}\text{C}$ |

\*  $l=5\text{mm}$  (body said)

- Electrical characteristics ( $T_a=25^{\circ}\text{C}$  Unless otherwise specified )

| Item                 | Symbol    | Conditions           | Max. | Unit |
|----------------------|-----------|----------------------|------|------|
| Forward voltage drop | $V_{FM}$  | $I_{FM}=3.0\text{A}$ | 0.8  | V    |
| Reverse current      | $I_{RRM}$ | $V_R=V_{RRM}$        | 5.0  | mA   |

**■ Characteristics**